



## FEATURES

- **5 Year Warranty**
- Microprocessor controlled movement
- 15 minutes of backup power (no batteries required)
- Accuracy to within  $\pm 1$  second of a master clock
- Reduced power consumption
- Attractive modern design
- Impact-resistant black plastic case
- Shatter-resistant polycarbonate crystal
- Diagnostic LED

## DESCRIPTION

The **american time™** AllSync Plus clocks are provided in **round only** high impact black plastic cases with clear polycarbonate crystals and bold, black numerals and minute markers on a non-yellowing white dial. Stylish hour and minute hands are aluminum with a black finish and a red sweep hand. Plastic case (bezel) also available in white or brown.

AllSync Plus clocks are designed to work with multiple master clocks and correction signals. This unit is programmed to identify the signal it receives from the master and operate as that style of clock. Changing clock operation from one style to another is as easy as unplugging the clock from one system and plugging it into another. If needed, changing the placement of two small jumpers on the circuit board can change the voltage required to run this clock from 120vac to 24vac or 24vac to 120vac. This clock provides 15 minutes of backup run power without the use of batteries. If a power outage should last longer than 15 minutes, the clock will synchronize to the master clock at the hourly and 12 hour correction cycles.

## Correction Signals

Works on:

- Hourly correction: 7-9 seconds starting at the 57th minute and 54th second. 12 hour correction: 13-18 seconds starting at 5:57:54 (am and pm).
- Hourly correction: 24-28.5 seconds starting at the 0 minute and 0 second. 12 hour correction: 24-32 minutes starting at 6:00:00 (am and pm).
- \*Hourly correction: 54-56 seconds starting at the 58th minute and 5th second. 12 hour correction: 10 pulses of 94-96 seconds starting at 5:05:00 (am and pm) and repeating every 2 minutes.
- Hourly correction: 24-26 seconds starting at 0 minute and 0 second. 12 hour correction: 25 pulses of 24-26 seconds starting at 6:00:00 (am and pm) and repeating every 60 seconds.
- Hourly correction: 63-67 seconds starting at the 58th minute and 0 second. 12 hour correction: 14 pulses of 63-67 seconds starting at 5:06:00 (am and pm) and repeating every 2 minutes.
- \*Hourly correction: 54-56 seconds starting at the 58th minute and 5th second. 12 hour correction: 12 pulses of 63-67 seconds starting at 5:05:00 (am and pm) repeating every 90 seconds.

## \*Note:

When switching between these correction protocols, you must use a different correction protocol to complete the transition. The AllSync Plus clock needs to distinguish between hourly corrections before it can change correction protocols internally.

## COMPLIANCE

- FCC Part 15 Class B
- ICES-003

**SPECIFICATIONS**

- 24vac/60 Hz or 120vac/60Hz
- Current draw: 24vac, 1 watt, .043 amps  
120vac, 3 watts, .028 amps

Maximum operating voltage: 24vac setting = 32vac  
120vac setting = 140vac  
Minimum operating voltage: 24vac setting = 18vac  
120vac setting = 105vac

**GENERAL**

Types of secondary clocks compatible with AllSync Plus:

- Cincinnati WS\*, \*D-8, \*D-10, \*D-12 Series
- Dukane 24SS\* Series, 240\* Series
- Edwards \*010 & \*012 Series
- Faraday 2315\*, 2316\*, 2335\*, 2336\*, 2380\*, 2382\*, 2310\*, 2320\*, 2330\*, 2313\*, 2314\*, 2333\*, 1310 through 1431 Series and 2420\* through 2431\* Series
- Honeywell ST402A\* Series
- Lathem Type SS\* Series
- National Time \*EX-HH and \*EX-LL Series
- Simplex® & IBM 77\* Series, 82\* Series, 2310 – 92\* Series, 6310 – 92\* Series

\*Indicates more numbers before or after.

**ORDERING INFORMATION**


Part #	Description
U45BAAA?04	10" Rd Flush 120vac
U45BABA?04	10" Rd Flush 24vac
U55BAAA?04	12" Rd Flush 120vac
U55BABA?04	12" Rd Flush 24vac
U65BAAA?04	15" Rd Flush 120vac
U65BABA?04	15" Rd Flush 24vac

**Note:**

Replace the ? in the part number with the number from the list below that will correspond with the system you're replacing. New flush mount installations require backboxes.

- 0 = Faraday      1 = National      5 = Simplex®      6 = Cincinnati/Edwards
- 7 = 2-hook      8 = Setco      9 = R&H (keyhole)

Flush mount plastic



**OUTSIDE DIMENSIONS  
FLUSH MOUNT**

SIZE	A	B
10"	9 <sup>7</sup> / <sub>8</sub> "	1 <sup>3</sup> / <sub>8</sub> "
12"	13 <sup>1</sup> / <sub>4</sub> "	2"
15"	16"	2"

At American Time, we continually strive to improve our products to meet our customers' needs and to provide the best possible value. The above specifications are believed to be correct, are subject to change without notice and may otherwise vary from the above. Please call if you need verification of any specifications or the suitability of a particular product for a particular application. © American Time