

**AllSet® Series
Battery Clocks
Wood Case**



Light Oak



Mahogany

FEATURES

- 5 Year Warranty
- Automatic adjustment for Daylight Saving Time
- Wood case with built-in hanger
- Available in two finishes
- Polycarbonate crystal
- Sweep second hand
- AA battery movement
- Battery Booster (optional)

GENERAL

The **american time**™ AllSet battery clocks, with optional Battery Booster, are ideal for schools, hospitals, and state and federal buildings. Clocks are provided in a round wood case with a shatter-resistant crystal and bold, black numerals and minute markers on a non-yellowing white dial. Stylish hour and minute hands are aluminum with a black finish and a red sweep hand.

DESCRIPTION

The AllSet quartz clock movement features a microchip with an internal battery that keeps track of the current date and time. The microchip is programmed to make the daylight saving time change at 03:00 am Eastern, 02:00 am Central, 01:00 am Mountain and 12:00 Pacific time twice a year. In the Spring, the movement will move the hands forward one hour, at an accelerated speed, to achieve the advance of one hour. In the Fall, the movement will automatically stop moving the hands for one hour and start ticking again when the clock is on time, to adjust back to standard time.

Clocks use a quartz-based battery movement which uses one AA alkaline battery. The optional Battery Booster holds six AA batteries in parallel which extends maintenance-free clock operating life 5+ years.

Note: Time must be manually set at startup and after replacing the batteries. Internal time/date is only used for moving hands for DST changes.

ORDERING INFORMATION


Part #	Description		With Battery Booster
Stand-Alone			
E56LGQD304	12" Light oak, surface		E56LGQD304BP
E56MGQD304	12" Mahogany, surface		E56MGQD304BP
E66LGQD304	15" Light oak, surface		E66LGQD304BP
E66MGQD304	15" Mahogany, surface		E66MGQD304BP

Note: Other dial styles available.

Note: Personalized dial option available. Add L to the end of the Part #.

SPECIFICATIONS

Operating voltage: 1.5vdc
 Operating voltage range: 1.3 to 1.7vdc
 Operating temp range: 14°F to 122°F (-10°C to +50°C)
 Accuracy typical: ±1 Sec/Day
 Nominal torque at 1.5vdc: 1.5 g/cm @ second shaft



OUTSIDE DIMENSIONS

SIZE	A	B
Surface		
12"	15¾"	2½"
15"	18½"	2½"

At American Time, we continually strive to improve our products to meet our customers' needs and to provide the best possible value. The above specifications are believed to be correct, are subject to change without notice and may otherwise vary from the above. Please call if you need verification of any specifications or the suitability of a particular product for a particular application. © American Time