

**Wireless 18" & 24" Analog
Steel Case Clocks
Electric**



SQ74BHAA989



SQ84BGAA989

GENERAL INFORMATION

- Clock hour & minute hands:..... Black
- Clock second hand: Red
- Crystal 18": Glass; 24": Polycarbonate
- Power: 120vac; 60 Hz
- Plug: 3 prong grounded, 6 ft. cord
4 position Molex® connector
- Rear panel indicator: LED1 - Red = No signal 2 minutes
Green = Signal last 2 minutes
..... LED2 - 1 Red Flash = HH:MM:00 (top of minute)
1 Green Flash = HH:00:00 (top of hour)
Flash Red/Green = Relay active
..... LED3 - 1 Yellow Flash = HH:MM:30 Signal
2 Yellow Flashes = HH:MM:00 Signal
- Receiver sensitivity: 10uV per meter
- Antenna type: External
- Time to synchronize: Minute hand within one hour; hour hand within 12 hours
- Time accuracy: ±1 second to SiteSync IQ® System Controller
- Warranty: Two Years

PHYSICAL / ENVIRONMENTAL SPECIFICATIONS

- Operating temperature: 41°F to 131°F
- Storage temperature: 41°F to 131°F
- Relative humidity: 0% - 95% Non-condensing

SPECIFICATIONS

Electrical requirements: 120vac 60 Hz 1 rpm 0.1amp peak

ORDERING INFORMATION

Part #	Description
SQ74BHAA989	18" Round, surface mount, 120vac
SQ84BGAA989	24" Round, surface mount, 120vac


Note: Personalized dial option available. Add L to the end of the Part #.
Note: These clocks are intended for use with a SiteSync IQ® Wireless Clock System.

BEZEL FINISH



Black Sand

Steel
surface mount



OUTSIDE DIMENSIONS

"A" Dimensions:
Round

19" for 18" clocks
24½" for 24" clocks

"B" Dimensions:
3¼" for 18" clocks
4¼" for 24" clocks

At American Time, we continually strive to improve our products to meet our customers' needs and to provide the best possible value. The above specifications are believed to be correct, are subject to change without notice and may otherwise vary from the above. Please call if you need verification of any specifications or the suitability of a particular product for a particular application. © American Time