



GENERAL INFORMATION

- Clock hour & minute hands: Black
- Clock second hand:..... Red
- Clock case:..... Aluminum
- Clock crystal:..... Polycarbonate
- Power: 6 (1.5V) AA Lithium batteries (included)
- Battery life:..... Up to 5 years
- Rear panel indicator: Red LED indicates receiver wake-up and time sync
- Receiver sensitivity: 10uV per meter
- Antenna type: External
- Time to synchronize: Initial sync time is 5-10 minutes
- Time accuracy: ±1 second to SiteSync IQ® Master Clock
- Warranty: Two Years

PHYSICAL / ENVIRONMENTAL SPECIFICATIONS

- Operating temperature: 41°F to 131°F
- Storage temperature:..... 41°F to 131°F
- Relative humidity: 0% - 95% Non-condensing

Note: These clocks are intended for use with a SiteSync IQ Wireless Clock System.


ORDERING INFORMATION

Part #	Description
SQ54AGDD304BP	12" surface, 04 dial style, Battery Booster
SQ64AGDD304BP	15" surface, 04 dial style, Battery Booster

Note: Other dial styles available

Add L to the end of the Part # for personalized dial option

Surface



OUTSIDE DIMENSIONS

SIZE	A	B
12"	13 ³ / ₈ "	2 ⁵ / ₈ "
15"	16 ¹ / ₄ "	2 ⁵ / ₈ "

At American Time, we continually strive to improve our products to meet our customers' needs and to provide the best possible value. The above specifications are believed to be correct, are subject to change without notice and may otherwise vary from the above. Please call if you need verification of any specifications or the suitability of a particular product for a particular application. © American Time