Wireless LED Message Board

GENERAL INFORMATION

Weight:	ATS112 - 8.5lbs.
	ATS120 - 15.3lbs.
Display:	ATS112 - 10 characters in single line mode; up to 40 characters in double line mode
	ATS120 - 20 characters in single line mode; up to 80 characters in double line mode
Line voltage:	120vac 60Hz
Current:	ATS112 - 0.20 amps at 120vac
	ATS120 - 0.30 amps at 120vac
Ambient operating range:	50°F to 120°F (10°C to 49°C)
Recommended storage temperature:	-22°F to 113°F (-30°C to 45°C) for six months maximum
Humidity:	85% RH at 30°C (86°F)
System compatibility:	Non-corrective
Frequency:	450-470MHz
Channel spacing:	12.5KHz
Character height:	4 3/4" in single line mode; 2" in two line mode
Array:	ATS112 - 160x16; ATS120 320x16
Time format:	12 or 24 hour selectable
Time adjustment:	Manual adjustment via wireless message
Buzzer:	Manually activated with 9 tones

ORDERING INFORMATION

Part #	Description
ATS112	28"w x 6 1/4"h x 2 3/4"d
ATS120	52"w x 6 1/4"h x 2 3/4"d

Note: This clock is intended for use with a SiteSync IQ® Wireless Clock System.

At American Time, we continually strive to improve our products to meet our customers' needs and to provide the best possible value. The above specifications are believed to be correct, are subject to change without notice and may otherwise vary from the above. Please call if you need verification of any specifications or the suitability of a particular product for a particular application.
© American Time

140 3rd St. S, PO Box 707, Dassel, MN 55325
800-328-8996 • american-time.com

PS03146 Rev B