american time

Wireless LED Message Board

Integrated Solutions



GENERAL INFORMATION

Weight: ATS112 - 8.5lbs.

ATS120 - 15.3lbs.

ATS120 - 20 characters in single line mode; up to 80 characters in double line mode

Line voltage: 120vac 60Hz

Current: ATS112 - 0.20 amps at 120vac

ATS120 - 0.30 amps at 120vac

Ambient operating range: 50°F to 120°F (10°C to 49°C)

Recommended storage temperature: -22°F to 113°F (-30°C to 45°C) for six months maximum

Humidity: 85% RH at 30°C (86°F)

System compatibility: Non-corrective
Frequency: 450-470MHz
Channel spacing: 12.5KHz

Array: ATS112 - 160x16; ATS120 320x16

Time adjustment: Manual adjustment via wireless message

Buzzer: Manually activated with 9 tones

ORDERING INFORMATION

Part # Description

ATS112 28"w x 6¹/₄"h x 2³/₄"d **ATS120** 52"w x 6¹/₄"h x 2³/₄"d

Note: This clock is intended for use with a SiteSync IQ® Wireless Clock System.

At American Time, we continually strive to improve our products to meet our customers' needs and to provide the best possible value. The above specifications are believed to be correct, are subject to change without notice and may otherwise vary from the above. Please call if you need verification of any specifications or the suitability of a particular product for a particular application.

© American Time