

Bell Guards

FEATURES

- Bright zinc plated
- Epoxy lacquer clear coat
- Multiple sizes
- Constructed with heavy gauge rods

GENERAL

american time[®] guards are designed to protect your equipment from inadvertent damage while maintaining optimum visibility. ATS stocks a wide variety of shapes and sizes for immediate delivery to you. Ask your customer service representative about our custom guards manufactured for the unique products you want to protect. Measurements are inside dimensions.

DESCRIPTION

american time[®] guards are plated and clear coated for corrosion resistance and optimal appearance. The finish on the guards is designed for protection wherever they are used, internal or external. Some of the guards are hinged for easy access to the product after attachment to the wall. Mounting hinges can be added to all other guards for additional cost. Call our customer service representatives for pricing. AT guards are manufactured with #3 gauge, (approx. .250" diameter), #6 gauge (approx. .200" diameter) or #8 gauge (approx. .150" diameter) wire material. Wire guards have welded tabs with mounting holes (designed to accept .250" diameter fastening lags, bolts or screws) or looping foot attachments for easy installation.

ORDERING INFORMATION

Model 4900

- 8³/₄" diameter x 4" deep (11 ga. rods)
- 2³/₄" x 4³/₄" hole openings
- Bell and smoke detector guard
- Wall or ceiling mount

Model G2009

- 9" x 9" x 6" deep (3 & 6 ga. rods)
- 2³/₄" square hole openings
- Bell guard

Model G2064

- 10¹/₂" x 8¹/₂" x 11" deep (3 ga. rods)
- 2¹/₂" x 3¹/₄" hole openings
- Bell, horn, strobe and speaker guard

Model G2002

- 11" x 11" x 6" deep (3 & 6 ga. rods)
- 2³/₄" square hole openings
- Bell guard

Model CFG103

- 14¹/₂" x 12¹/₂" x 5¹/₂" deep (back opening, inside square dimensions) 19⁵/₈" x 14¹/₄" x 6" (overall dimensions)
- Designed for outdoor use
- Heavy-duty 18 gauge steel
- Weather-resistant black powder coat finish
- Slanted front with grill for optimal output



4900



G2009

G2002





At American Time, we continually strive to improve our products to meet our customers' needs and to provide the best possible value. The above specifications are believed to be correct, are subject to change without notice and may otherwise vary from the above. Please call if you need verification of any specifications or the suitability of a particular product for a particular application.