

## SiteSync IQ® Wireless Signal Indicator with 9v Battery

### GENERAL INFORMATION

- Power: ..... One 9volt battery (included)
- RF Frequency: ..... 450-470 MHz (factory set)
- Receiver Sensitivity: ..... -110dBm
- Operating Temperature Range: .. 41°F to 131°F
- Relative Humidity: ..... 0%-95% non-condensing
- Antenna Type:..... External
- Warranty: ..... 2 Years



**Part # H004292**

The SiteSync IQ Wireless Signal Indicator allows the user to monitor the wireless signal from the transmitter of the SiteSync IQ system controller. The Signal LED flashes green to indicate the system controller is transmitting a signal. A red LED indicates no signal reception from the system transmitter (attention is required to check system operation).

The four Signal Strength LEDs are used to represent the RSSI (Received Signal Strength Indication) value at the location of last reception. These LEDs will remain on for 20 seconds after the last page received.

- 4=Excellent
- 3=Good
- 2=Adequate
- 1=Weak

At American Time, we continually strive to improve our products to meet our customers' needs and to provide the best possible value. The above specifications are believed to be correct, are subject to change without notice and may otherwise vary from the above. Please call if you need verification of any specifications or the suitability of a particular product for a particular application. © American Time