



# AllSync Plus Wood Case

AllSync Plus clocks are designed to work with multiple master clocks and correction signals. This unit is programmed to identify the signal it receives from the master and operate as that style of clock. Changing clock operation from one style to another is as easy as unplugging the clock from one system and plugging it into another. If needed, changing the placement of two small jumpers on the circuit board can change the voltage required to run this clock from 120vac to 24vac or 24vac to 120vac. This clock provides 15 minutes of backup run power without the use of batteries. If a power outage should last longer than 15 minutes, the clock will synchronize to the master clock at the hourly and 12 hour correction cycles.

## FEATURES

- 3 Year Warranty
- Microprocessor controlled movement
- 15 minutes of backup power (no batteries required)
- Accuracy to within  $\pm 1$  second of system controller
- Automatic Daylight Saving Time adjustment
- Reduced power consumption
- Security bracket included
- Wood case in two colors
- Polycarbonate crystal
- Diagnostic LED

## Correction Signal Compatibility

- Hourly correction: 7-9 seconds starting at the 57th minute and 54th second. 12-hour correction: 13-18 seconds starting at 5:57:54 (am and pm).
- Hourly correction: 24-28.5 seconds starting at the 0 minute and 0 second. 12-hour correction: 24-32 minutes starting at 6:00:00 (am and pm).
- \*Hourly correction: 54-56 seconds starting at the 58th minute and 5th second. 12 hour correction: 10 pulses of 94-96 seconds starting at 5:05:00 (am and pm) and repeating every 2 minutes.
- Hourly correction: 24-26 seconds starting at 0 minute and 0 second. 12 hour correction: 25 pulses of 24-26 seconds starting at 6:00:00 (am and pm) and repeating every 60 seconds.
- Hourly correction: 63-67 seconds starting at the 58th minute and 0 second. 12 hour correction: 14 pulses of 63-67 seconds starting at 5:06:00 (am and pm) and repeating every 2 minutes.
- \*Hourly correction: 54-56 seconds starting at the 58th minute and 5th second. 12 hour correction: 12 pulses of 63-67 seconds starting at 5:05:00 (am and pm) repeating every 90 seconds.

**\*Note:** When switching between these correction protocols, you must use a different correction protocol to complete the transition. The AllSync Plus clock needs to distinguish between hourly corrections before it can change correction protocols internally.

## COMPLIANCE

- FCC Part 15 Class B
- ICES-003



Light Oak



Mahogany

## SPECIFICATIONS

Clock hour & minute hands	Black
Clock second hand	Red
Clock case	Wood (2 options)
Clock crystal	Polycarbonate
Power	120VAC 50/60 Hz or 24VAC 50/60 Hz
Maximum operating voltage	24VAC setting = 32VAC 120VAC setting = 140VAC
Minimum operating voltage	24VAC setting = 18VAC 120VAC setting = 105VAC
Time accuracy	±1 second to SNTP time server.
Current draw	24VAC, 1 watt, .043 amps 120VAC, 3 watts, .028 amps
Warranty	3 Years

## GENERAL

Types of secondary clocks compatible with AllSync Plus:

Cincinnati	WS*, *D-8, *D-10, *D-12 Series
Dukane	24SS* Series, 240* Series
Edwards	*010 & *012 Series
Faraday	2315*, 2316*, 2335*, 2336*, 2370*, 2372*, 2380*, 2382*, 2311*, 2320*, 2331*, 2314*, 1310 through 1431 Series and 2420* through 2431* Series
Honeywell	ST402A* Series
Lathem	Type SS* Series
National Time	*EX-HH and *EX-LL Series
Simplex® & IBM	77* Series, 82* Series, 2310 – 92* Series, 6310 – 92* Series


\*Indicates more numbers before or after.

## ORDERING INFORMATION

Part #	Description	24VAC
<b>120VAC</b>		
U54LGAA304	12" Light Oak, Surface	U54LGBA304
U54MGAA304	12" Mahogany, Surface	U54MGBA304
U64LGAA304	15" Light Oak, Surface	U64LGBA304
U64MGAA304	15" Mahogany, Surface	U64MGBA304

**Note:** Other dial styles available.

Add L to the end of the Part # for personalized dial option.



## OUTSIDE DIMENSIONS

SIZE	A	B
<b>Surface</b>		
12"	15 <sup>3</sup> / <sub>4</sub> "	2 <sup>7</sup> / <sub>8</sub> "
15"	18 <sup>1</sup> / <sub>2</sub> "	2 <sup>7</sup> / <sub>8</sub> "

At American Time, we continually strive to improve our products to meet our customers' needs and to provide the best possible value. The above specifications are believed to be correct, are subject to change without notice and may otherwise vary from the above. Please call if you need verification of any specifications or the suitability of a particular product for a particular application.

© American Time